

767 Series Stopper Plugs

Cable Gland Accessories

Increased Safety and Flameproof.

Zone 1 and 2, Zone 21 and 22
Gas (G) and Dust (D)

Applications

- Stopper plug is designed for use from the outside of the enclosure to permanently or temporarily close any unused entries.
- Idea for use on flameproof, increased safety electrical equipment in hazardous areas.
- In general, care should be taken to ensure that a suitable entry thread sealing washer is also selected and installed, where applicable, to ensure that an effective seal is made at the entry, thereby maintaining the integrity of the enclosure or equipment I.P. rating.

Features

- Catering to both Industrial and Hazardous Area applications the range covers a number of different metallic and non-metallic (e.g. Nylon) forms.
- Features a dome head with an Allen Key.
- Optional integral entry thread "O" Ring seal is available.

Standard Materials

- Brass fully nickel plated

Options

- Aluminum: replace suffix -5 with 1
- 316L stainless steel: replace suffix -5 with 4
- Nylon: replace suffix -5 with 2
- Optional O-Ring: replace **D** with **DR**
- IP68 when fitted with an O-Ring entry thread sealing washer



ATEX/IECEX Certifications and Compliances

- **Certification Type 767**
 - Gas: Zones 1
 - Type of Protection: Ex d IIC Gb (except Nylon), Ex e IIC Gb
 - Dust: Zone 20
 - Type of Protection: Ex ta IIC Da
 - Conforming to ATEX 94/9/CE: Ⓢ II 2G 1D
 - Operating Temperature: -60 °C to +200 °C (Metallic) and -20 °C to +60 °C (Nylon)
 - CE Declaration of Conformity: DC07001
 - ATEX Certificate: Sira 13ATEX1265X
 - IECEx Certificate: IECEx SIR 13.0094X
 - Other Certifications: UL, cCSAus
 - Marine Approval: LLOYDS, DNV, ABS
 - Index of Protection according EN/IEC 60529: IP66 or IP68 with seal

INMETRO Certification


- INMETRO Certificate: TÜV 12.1333X

EURASEC Certification

- TC RU C-GB.ГБ.05.B.00138

	Male Thread Size	Allen Key size A/F	Head diameter in mm	Nickel Plated Brass Catalog Number
	M16	M8	22.0	767DM15
	M20	M10	27.0	767DM25
	M25	M10	30.0	767DM35
	M32	M10	36.0	767DM45
	M40	M10	46.0	767DM55
	M50	M10	55.0	767DM65
	M63	M14	65.0	767DM75
	M75	M14	80.0	767DM85
	M90	M14	95.0	767DM95
	1/2"NPT			767DT15
	3/4"NPT			767DT25
	1"NPT			767DT35
	1-1/4"NPT			767DT45
	1-1/2"NPT			767DT55
	2"NPT			767DT65
	2-1/2"NPT			767DT75
	3"NPT			767DT85

Optional 'O' Ring ①



Mushroom Head Stopper Plug

① For optional O-Ring, change **D** to **DR** in catalog number. Contact your factory representative for price and availability.