

DATA SHEET IL-60 NIMH HAND LAMP

MODEL	IL-60 NiMH
Product description	Rechargeable hand lamp
DNV Certification	E-11962
Operating temperature	-20°C +40°C
Light source	Halogen bulb G4 6W / 10W / 20 W, lifetime: 100 h
Light output	6 W 120 lm
	10 W 200 lm
	20 W 440 lm
Operating time	Full power: Low power:
	6 watt = 8 h 6 watt = 12 h
	10 watt = 5 h
_	20 watt = 2 h 30min 20 watt = 4 h
Beam type	Narrow or Medium
Lens	Tempered glass 108 mm x 5 mm
Enclosure	High impact polyamide
Ingress protection	IP 67
Colour	Yellow body / Black locking ring
_	Other colours on request.
Power source	6V Rechargeable NiMH battery
Weight with battery	1,4 kg
Dimensions	Approx. 215 mm (L) x 120 mm (W) x 125 mm (H)
Charging time	11 h
Other features	Battery capacity indicator
	Deep discharge prevention
	Low battery warning
	Shoulder strap
Chargers	MICA ILC4-VAC Single mains charger (85264VAC)
	MICA ILC4 Single vehicle charger (1224VDC)
	MICA CR-C3 Multi charger for 3 lamps (100240VAC) MICA CR-C5 Multi charger for 5 lamps (100240VAC)
Accessories	Colour filters: red, green and amber
Accessories	Diffuser filter
	Square light beam filter
	Infra-red lens 850 nm
	Adjustable stand for a single lamp
	MICA IL-holder for up to 8 lamps
	MIGATE Holder for up to origings





