

Unicode™ 2 Series – Polyamide control stations (Zones 1 & 2 – 21 & 22)

	Ex de IIC	Catalogue Number ①②
	Momentary push button with green "I" or red "O" insert (NO+NC) – 2x M20 entries	U41W2A3
	Emergency stop mushroom head push-pull button (NO+NC) – 2x M20 entries	U41W2D3
	Emergency stop mushroom head with key release (NO+NC) – 2x M20 entries	U41W2C3
	Key push button, key removable in both positions (NO+NC) – 2x M20 entries	U41W2E3
	2 fixed position selector switch (NO+NC) – 2x M20 entries	U41W2H3
	3 fixed position selector switch "I-0-II" (2 NO) – 2x M20 entries	U41W2J1
	Green pilot light 12 to 254 Vac, 12 to 60 VDC – 2x M20 entries	U41W2PR
	Red pilot light 12 to 254 Vac, 12 to 60 VDC – 2x M20 entries	U41W2PG
	Green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U42W2A3A3
	Green push button "I" (NO+NC) and red emergency stop mushroom head (NO+NC) – 2x M20 entries	U42W2A3D3
	Green pilot light and green push button "I" (NO+NC) – 2x M20 entries	U42W2PGA3
	Red pilot light and red push button "O" (NO+NC) – 2x M20 entries	U42W2PRA3
	Ammeter 48x48 mm, 1A current transformer, with 0-1-3 scale – 2x M20 entries	U42W2VA13
	Green push button "I" (NO+NC), red push button "O" (NO+NC) and red emergency stop mushroom head (NO+NC) – 2x M20 entries	U43W2A3A3D3
	Green indicator light and green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U43W2PGA3A3
	Red indicator light and green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U43W2PRA3A3
	Ammeter 48x48 mm, 1A current transformer, with 0-1-3 scale, green push button "I" (NO) and red push button "O" (NC) – 2x M20 entries	U43W2VA13A5A9
	Ammeter 48x48 mm, 1A current transformer, with 0-1-3 scale and 3 position selector switch with spring return "II-0" (NO+NC) – 2x M20 entries	U43W2VA13M3

Note: Unicode 2 Series exists also in inox 316L version. Please refer to the Appleton catalogue, www.appletonelec.com

① For additional configurations, please refer to the Appleton catalogue, www.appletonelec.com.

② Two entries diameter 20 mm, blanking plug, cable gland for unarmoured cables and two locknuts.

Unicode 2 Series – Polyester control stations (Zones 1 & 2 – 21 & 22)

	Ex de IIC	Catalogue Number ① ②
	Momentary push button with green "I" or red "O" insert (NO+NC) – 2x M20 entries	U21W2A3
	Green momentary push button "I" (NO) – 2x M20 entries	U21W2A5
	Green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U21W2A3A3
	Emergency stop mushroom head push-pull button (NO+NC) – 2x M20 entries	U21W2D3
	Emergency stop mushroom head with key release (NC) – 2x M20 entries	U21W2C3
	Key push button, key removable in both positions (NO+NC) – 2x M20 entries	U21W2E3
	Green pilot light and red pilot light – 2x M20 entries	U21W2PGPR
	2 fixed position selector switch (NO+NC) – 2x M20 entries	U21W2H3
	3 fixed position selector switch "I-0-II" (2 NO) – 2x M20 entries	U21W2J1
	Green push button "I" (NO) and red push button "O" (NC) – 2x M20 entries	U22W2A5A9
	Green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U22W2A3A3
	Green push button "I" (NO) and red emergency stop mushroom head (NC) – 2x M20 entries	U22W2A5D9
	Green push button "I" (NO+NC) and red emergency stop mushroom head (NO+NC) – 2x M20 entries	U22W2A3D3
	Green pilot light and green push button "I" (NO+NC) – 2x M20 entries	U22W2PGA3
	Red pilot light and red push button "O" (NO+NC) – 2x M20 entries	U22W2PRA3
	Green indicator light, red indicator light "I" (NO) green push button and red push button "O" (NC) – 2x M20 entries	U22W2PGPRA5A9
	Ammeter 48x48 mm, 1A current transformer, with 0-1-3 scale and 3 position selector switch with spring return "II-0" (NO+NC) – 2x M20 entries	U22W2VA13M3
	Green push button "I" (NO), red push button "O" (NC) and red emergency stop mushroom head (NC) – 2x M20 entries	U23W2A5A9D3
	Green indicator light and green push button "I" (NO+NC) and red push button "O" (NO+NC) – 2x M20 entries	U23W2PGA3A3
	Red indicator light and red push button "I" (NO+NC) and green push button "O" (NO+NC) – 2x M20 entries	U23W2PRA3A3

Note: Unicode 2 Series exists also in inox 316L version. Please refer to the Appleton catalogue, www.appletonelec.com

① For additional configurations, please refer to the Appleton catalogue, www.appletonelec.com.

② Two entries M20 with threaded earth brass plate, blanking plug, cable gland for unarmoured cables.