

<b>MODEL</b>	<b>ILC</b>
<b>Product description</b>	Single vehicle charger
<b>Certification</b>	e17*72/245*2006/28*0124*02
<b>Input voltage</b>	12...24VDC
<b>Charging temperature</b>	0°C ... +40°C
<b>Charge current</b>	800mA
<b>Trickle charge current</b>	100mA
<b>Enclosure</b>	High impact PA / Aluminium
<b>Weight</b>	485 g
<b>Dimensions</b>	Approx. 153 mm (L) x 138 mm (W) x 88 mm (H)
<b>Mounting</b>	Wall mounted vertical or horizontal
<b>Compatible product</b>	IL-600, IL-6000 GT, IL-60, IL-80 ATEX LED, IL-800
<b>Charging time</b>	<b>11 h:</b> IL-60 NiMH, IL-600 NiMH, IL-6000 GT NiMH 9,0A <b>7 h:</b> IL-60 NiCd, IL-600 NiCd <b>6 h:</b> IL-80 ATEX LED NiMH, IL-800 NiMH
<b>Charging features</b>	Sophisticated recharge and battery protection: Charging curve control Ambient temperature control
<b>Accessories</b>	<b>MICA IL-2</b> mains adapter <b>MICA CR-13</b> power supply for max. 3 ILC chargers <b>MICA CR-15</b> power supply for max. 5 ILC chargers <b>MICA VAC-VDC</b> changeover unit from car battery <b>MICA</b> cigarette lighter cable

