

MODEL	ML-808 ATEX, ML-808 ATEX EM	
Product description	ML-808 ATEX: Rechargeable safety hand lamp ML-808 ATEX EM: Rechargeable emergency safety lamp	
Certification	ATEX: VTT 13 ATEX 024 Issue 1 II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135 °C Db	
Area of operation	Gas: zones 1 and 2 Dust: zones 21 and 22	
Temperature classification	Gas: T4 Dust: 135°C	
Operating temperature	-20°C ... +40°C	
Light source	1 high luminous Cree LED, lifetime: 50 000hrs	
Light output	Full power Over 100 lm	Low power 25 lm
Operating time	Full power: 4 hours 30 min	Low power: 15 hours
Beam type	Spot beam	
Lens	Tempered glass 41,5 x 3,2 mm	
Enclosure	Dissipative (antistatic) polypropylene + aluminium, impact resistant	
Ingress protection	IP 65	
Power source:	6V rechargeable NiMH battery	
Weight with battery	0,40 kg	
Dimensions	120 mm (H) x 63 mm (W) x 54 mm (L)	
Charging time	2 h 30 min	
Other features	Deep discharge prevention Battery capacity indicator low battery warning Wrist strap	
Chargers	MICA MLC Single fast charger (12..24VDC)	

